



www.rvhcctv.com

Model NO.	RV-BZ200VIPC	RV-BZ200VIPC-WF	RV-BZ200VIPC1	RV-BZ200VIPC1-WF
Sensor	SC2135			
DSP	Hi318EV200			
Resolution	1920*1080			
Rotation range	Pan 0°-180° ,Tilt 0°~55°			
Rotaion speed	Pan 0-20°/s,Tilt 0-12°/s			
IR range	50M			
IR control	PWM			
Preset	No support			
Motion detectin	Yes			
WDR	WDR			
Lens	3.6mm		2.8-12mm	
TF Card	No support	option, The biggest 64G	No support	option, The biggest 64G
WIFI	No support	Yes	No support	Yes
Compression	H.264/H.265M-JPEG			
Audio in	G711, 1CH (option)			
Audio Out	1 audio (Optional)			
P2P	android、Iphone			
Alarm	No support			
Protocol	TCP/IP, DHCP, NTP,UDP, SMTP, RTSP, ARP, DDNS, PPPoE,			
Compatibility	HIKVISION ,DAHUA, XM NVR , Milestone and AXXON platform			
Onvif	Support			
Power	DC12V(2A)			
POE	No support			
Temperature	-40℃~+60℃			
Consumption	≤15W			
Connector	RJ45			
protection level	IP66			
Package Size	168(W)*68(H)*68(D)mm			