



|                         |  |
|-------------------------|--|
| <b>Camera</b>           | <b>RV-D36VIP300</b>  |
| Image Sensor            | SC4236   |
| Main processor          | HI3516EV300  |
| Resolution              | 3.0MP  |
| Effective Pixels        | 2304×1296  |
| Compression             | H.265+/H.265/H.264/MJPEG   |
| TV System               | PAL/NTSC   |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec  |
| Min Illumination        | 0.001Lux   |
| S/N Ratio               | ≥52dB  |
| Scanning System         | Progressive  |
| Video Output            | Network  |
| <b>Night Vision</b>     |  |
| Infrared LED            | 14MIL x 24PCS  |
| Infrared Distance       | 30M  |
| IR Status               | Under 10 Lux By CDS  |
| IR Power On             | CDS Auto Control   |
| <b>LENS</b>             |  |
| Length                  | 2.8-12mm   |
| Pixels                  | 4MP  |
| <b>Network</b>          |  |
| Ethernet                | RJ-45 (10/100Base-T)   |
| Protocol                | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP                                |
| ONVIF                   | Support ONVIF 2.4  |
| P2P                     | optional   |
| POE                     | Optional, Support IEEE 802.3af   |
| Audio                   | optional   |
| WIFI                    | N/A  |
| Video Delay             | 0.3S (Within the Lan)  |
| IE Brower               | IE8-11, Google Chrome, Firefox, Safari, Mac Safari   |
| <b>Camera Features</b>  |  |
| Day/Night               | Color/ B&W (IR-CUT )   |
| Image Config            | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| BLC                     | Support  |
| WDR                     | Support  |
| Motion Detection        | Support  |
| Privacy Masking         | 3 Rectangular Zone   |
| Recording Mode          | NVR/UC ( Option,VMS)/Web   |
| Language                | Chinese Simplified, Chinese Traditional, English,  |
| Housing                 | Metal  |
| IR Cut Filter           | YES  |
| Operation Temperature   | -30℃ ~ +60℃ RH95% Max  |
| Storage Temperature     | -40℃ ~ +60℃ RH95% Max  |
| Power Source            | DC12V±10%, 600mA   |
| Dimension               | ∅ 150 x 90(H) mm   |
| Weight                  | 900g   |