



<b>Camera</b>	<b>RV-LAS24AHDC4</b>
Image Sensor	1/3.2" CMOS GC4603
Image Resolution	2576 *1456
Effective Pixels	4.0MP
TV System	PAL/NTSC
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s
S/N Ratio	≥50dB
Scanning System	Progressive Scan
<b>Lens</b>	
Manual Lens	3.6mm
Pixels	4MP
Auto Iris Support	NO
<b>Night Vision</b>	
Infrared LED	14MIL*18PCS
Infrared Distance	20M
IR Status	Under 10 Lux by CDS
IR Power On	CDS Auto Control
<b>Camera Features</b>	
Starlight	/
Day/Night	Yes
OSD Menu Language	Yes
White Balance	AUTO / MANUAL
Gain Control	AUTO
Noise Reduction	3DNR
Picture Adjustment	Yes
WDR	Yes
OSD Support	Option
UTC	Yes
Dip Switch	Option
<b>General</b>	
Housing	Plastic
housing color	white
Dual Voltage	DC-12V
IR Cut Filter	YES
Heater	/
Audio	/
Operation Temperature	-20℃ ~ +50℃ RH95% Max
Storage Temperature	-30℃ ~ +50℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	∅ 94x 69(H) mm
Weight	400g