



|                         |  |
|-------------------------|--|
| <b>Camera</b>           | <b>RV-LDS24NIP200H</b>   |
| Image Sensor            | IMX307   |
| Main processor          | HI3516EV200  |
| Resolution              | 2.0MP  |
| Effective Pixels        | 1920*1080  |
| Compression             | H.265+/H.265/H.264/MJPEG   |
| TV System               | PAL/NTSC   |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec  |
| Min Illumination        | 0.001Lux   |
| S/N Ratio               | ≥52dB  |
| Scanning System         | Progressive  |
| Video Output            | Network  |
| <b>Night Vision</b>     |  |
| Infrared LED            | 12MIL x3PCS  |
| Infrared Distance       | 20M  |
| IR Status               | Under 10 Lux By CDS  |
| IR Power On             | CDS Auto Control   |
| <b>LENS</b>             |  |
| Length                  | star level Lens3.6mm   |
| Pixels                  | 3MP  |
| <b>Network</b>          |  |
| Ethernet                | RJ-45 (10/100Base-T)   |
| Protocol                | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP                                |
| ONVIF                   | Support ONVIF 2.4  |
| P2P                     | optional   |
| POE                     | Optional, Support IEEE 802.3af   |
| Audio                   | optional   |
| WIFI                    | N/A  |
| Video Delay             | 0.3S (Within the Lan)  |
| IE Brower               | IE8-11, Google Chrome, Firefox, Safari, Mac Safari   |
| <b>Camera Features</b>  |  |
| Day/Night               | Color/ B&W (IR-CUT )   |
| Image Config            | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| BLC                     | Support  |
| WDR                     | Support  |
| Motion Detection        | Support  |
| Privacy Masking         | 3 Rectangular Zone   |
| Recording Mode          | NVR/UC ( Option,VMS)/Web   |
| Language                | Chinese Simplified, Chinese Traditional, English,  |
| Housing                 | Plastic  |
| IR Cut Filter           | YES  |
| Operation Temperature   | -20℃ ~ +50℃ RH95% Max  |
| Storage Temperature     | -30℃ ~ +50℃ RH95% Max  |
| Power Source            | DC12V±10%, 600mA   |
| Dimension               | ∅ 110 x 93(H) mm   |
| Weight                  | 500g   |