



| | |
|-------------------------|------------------------------------------------------------------------------------------------|
| Camera | RV-MN2NIP200E |
| Image Sensor | IMX307 |
| Main processor | HI3516EV200 |
| Resolution | 2.0MP |
| Effective Pixels | 1920*1080 |
| Compression | H.265+/H.265/H.264/MJPEG |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec |
| Min Illumination | 0.001Lux |
| S/N Ratio | ≥52dB |
| Scanning System | Progressive |
| Video Output | Network |
| Night Vision | |
| Infrared LED | |
| Infrared Distance | |
| IR Status | Under 10 Lux By CDS |
| IR Power On | CDS Auto Control |
| LENS | |
| Length | star level Lens3.7mm |
| Pixels | 3MP |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| ONVIF | Support ONVIF 2.4 |
| P2P | optional |
| POE | Optional, Support IEEE 802.3af |
| Audio | optional |
| WIFI | N/A |
| Video Delay | 0.3S (Within the Lan) |
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari |
| Camera Features | |
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| BLC | Support |
| WDR | Support |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/UC (Option,VMS)/Web |
| Language | Chinese Simplified, Chinese Traditional, English, |
| Housing | Metal |
| IR Cut Filter | YES |
| Operation Temperature | -30℃ ~ +60℃ RH95% Max |
| Storage Temperature | -40℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%, 600mA |
| Dimension | 36(W)x36(H)x27(D)mm |
| Weight | 300g |