



Camera	RV-ABZ100IP-10MX
Sensor	1/2.9"SONY IMX323
Output pixel	1920x1080
Lens	5.1-51mm
D/N	IR-CUT
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P
Software Control	IE, CMS, Management Platform
Video compression	H.264/H.265/M-JPEG
audio compression	G711, PCM
Mobile View(optional)	Android iPhone
Rotation Range	Pan:0°~220° , Tilt:-45°~25°(Manual)
Rotation Speed	Pan:0~30°/s
Preset Points	220pcs presets (dwell time 01-60s interval available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
AB scan range	Any point in Pan range: 0°~200°
AB scan speed	1-9 grades
Operating temperature	Outdoor: -40℃~+60℃
Operation menu	English
Humidity	≤95% Non Condensing
Consumption	≤15W
IR parameters	
Auto Control IR LED	PWM
IR distance	Up to 100 meters
LEDs	6 PCS Array 42Mil IR LED
Support ambient light detection	IR illumination on 1-9 grades selectable