



RV-HK36AHDt-KIT	
XVR	1x RV-1108AA5XVR
Camera	4 x RV-HK36AHDt
Cable	4x 18.5m BNC+DC Cable, 1x (1 to 5CH power cable splitter)
Mouse	1xUSB 2.0 Mouse
Hard Disk	No (Option)
Adaptor	1xDC12V/5A
Weight	7.6kg/SET
<b>Camera Model</b>	<b>RV-HK36AHDt</b>
Image Sensor	1/2.9" CMOS Sensor
Image Resolution	2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	AUTO
Scanning System	Progressive Scan
Audio	yes
<b>Lens</b>	
Focus Length	3.6mm(option 2.8mm)
Focus Control	Fixed
Lens Type	Fixed
<b>Night Vision</b>	
IR Cut Filter	YES
SMART IR LED	14μ x 24PCS
Infrared Distance	30M
IR Status	AGC Auto Control
<b>Camera Features</b>	
Starlight	/
Day/Night	YES
OSD Menu	Option
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO
<b>General</b>	
Housing	Metal, IP66
Bracket	YES
Operation Temperature	-20℃ ~ +50℃ RH95% Max
Storage Temperature	-30℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	195(W)x59(H)x60(D)mm
Weight	650g
<b>Model</b>	<b>RV-1108AA5XVR</b>
<b>System</b>	
Main Processor	Hi3520D V400+ TP2828(16M+2G)
Operating System	Embedded LINUX
<b>Video</b>	
Input	Analog: 4*5M-N
	Analog+Network: 2*Analog(5M-N)+2*1080P network
	Network: 4*1080P
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/Network, <b>TVI2.0 Support Audio</b>
Output	1HDMI,1 VGA
<b>Audio</b>	
Input	1 Channel, RCA
Two-way Audio	YES
Output	1 Channel, RCA

<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel in pure network mode
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications(motion detection)
Email Alarm	Send Image to The Designated E-mail
<b>PTZ</b>	
interface	1*485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
<b>Display</b>	
VGA	Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
HD Output	Resolution:1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
Display Split	4 Channel / 1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Recording</b>	
Video Compression	H.265
Audio Compression	G.711u
Resolution	Half 1080P(960×1080);720P(1280×720);960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Analog: Half 5M-N (4*12fps) , 1080P(960x1080 4*25fps),720P(1280x720 4*25fps), 960H(P:960x576 4*25fps/N:960x480 4*30fps) Pure IP: PAL :1080P@4x25fps, 960P@4x25fps, 720P@4x25fps, D1@4x25fps NTSC:1080P@4x30fps, 960P@4x30fps, 720P@4x30fps, D1@4x30fps
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Decode Capability	4CH 5M-N@8fps
Sync Playback	Pure Analog: 4CH 5M-N@5fps Mixture mode: 2CH 1080P@30fps+2CH 5M-N@8fps Pure Network: 4CH 1080P@30fps,
Remote Playback	1Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smart Phone Playback	4 Channel
Backup Mode	USB Device(with format FAT 32 )/Network
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES, ZEBEYE, HDPROVN
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~25fps)
Smart Phone	iPhone, ipad, Android ,Android pad
<b>Hard Disk Driver</b>	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
<b>General</b>	
Language	Chinese Simplified, Chinese Traditional, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, slonvennina, Dutch, Greek, Vietnamese,Bahasa indonesia
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V ≤6W (Without Hard Disk)
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	260*215*43(mm)
Weight	3kg (Without HDD)