



Camera	RV-VR21AIP
Solution	GM8135S +SC1135 1/3" Progressive Scan CMOS
Lens	Fish eye wide-angle lens, f=1.44mm
Angle	360°
Resolution	1.3MP
Sensitivity	0.2Lux @F2(colorful)/0.02Lux @F2(night vision)
Day /night conversion mode	Auto ICR
Video compression mode	H.264, double stream bit
Video frame	25ftp/sec
Image resolution	Max 1280×960
Audio coding	ADPCM, support 2-way audio interface
Communication interface	1 RJ45 10M/100M adaptive Lan port
Wireless standard	IEEE802.11b/g/n
Frequency range	2.4GHz~2.4835 GHz
Power interface	Micro USB
Storage interface	1TF Card (Micro SD) slot, max 64GB
Reset interface	One key reset
Power supply	DC12V, 1A
Working condition	-10°C~+50°C@humidity, 10%~ 95% no condensation
APP	Support IOS/Android system
	Support viewing real-time video and playback in the mobile
	Support local screenshots in the mobile phone ;
	Support alarm information screenshot push ;
	Support 2-way audio interface ;
	Support cloud storage ;
	Support 5 view modes (3D mode, traditional mode, mixed mode, corridor mode, panoramic inversion mode);