



Camera	RV-Z42NIP200H
Image Sensor	IMX307
Main processor	HI3516EV200
Resolution	2.0MP
Effective Pixels	1920*1080
Compression	H.265+/H.265/H.264/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Min Illumination	0.001Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Night Vision	
Infrared LED	42MIL x4PCS
Infrared Distance	80M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
LENS	
Length	star level Lens3.6mm
Pixels	3MP
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	optional
POE	Optional, Support IEEE 802.3af
Audio	optional
WIFI	N/A
Video Delay	0.3S (Within the Lan)
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/UC (Option,VMS)/Web
Language	Chinese Simplified, Chinese Traditional, English,
Housing	Metal
IR Cut Filter	YES
Operation Temperature	-30℃ ~ +60℃ RH95% Max
Storage Temperature	-40℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 600mA
Dimension	213(W) x93(H) x83(D)mm
Weight	1000g