RV-MNKNIP200 2MP 2 Inch Outdoor Mini PT Dome



Features:

- 2MP 1/3.2" low illumination CMOS sensor;
- Advanced 28NM process with lower HD power consumption, stable and reliable 1080P resolution, clear and delicate images;
- HD lens 3.6mm@F2.0:
- ICR automatic switching for day and night monitoring;
- Automatic electronic shutter to adapt to different monitoring environments;
- Infrared distance: 4 high-power LED lights 4 white lights 15m~20m;
- Support D-WDR, 3D noise reduction;
- H.265Al Video compression technology, high image quality, low bit rate;
- Support mobile phone remote monitoring (iOS, Android);
- Multi-browser access (IE、Chrome、Firefox、 Safari);
- Support information overlay (ID, IP, DDNS..);
- Supporting WEB、CMS、VMS、MYEYE、cloud service;
- Supports interfacing with HVR/NVR and supports standard Onvif protocol.;

Application scenario:

Suitable for roads, warehouses, underground parking lots, bars, pipelines, parks. A place where the light is dark or unlit and requires high definition quality.

	Model No.	RV-MNKNIP200
Camera	Sensor+DSP	SC2235E + XM530AI
	Minimum	Colour: 0.01Lux @(F1.2,AGC ON); 0 Lux
	illumination	B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux
	Shutter	1/50(1/60)s to 1/10,000s
	Lens	HD lens 3.6mm@F2.0
	Mount Type	M12
	Day Night	Support IR-CUT
Image	Maximum	1920*1080
	image size	1320 1000
	iiilage size	DAI 4000D 005f
	Frame rate	PAL: 1080P@25fp
		NTSC: 1080P@30fps
	Image settings	Saturation, brightness, contrast
		adjustable through the client or browser
Compression standard	Standard	H.264X/H2.65Al Video compression
	Compressed	0.1Mbps~4Mbps
	output code	
	Audio	G711A
	compression	
Network Function	Storage	Network Storage
	Intelligent	Motion detection, video loss, network
	alarm	cable break, IP address conflict
	Support	Wi-Fi wireless transmission (supports
	Protocol	IEEE802.11b/g wireless protocol)
	General	Anti-flicker, dual stream, heartbeat,
	Function	password protection
	Audio I/0	Build in 3W speaker
General	Operating	-20°C- + 60°C
	temperature	
	Working	10%-90% RH
	humidity	
	Power Supply	DC12V±10%
	IR Distance	4 high-power LED lights 4 white lights
	Power	MAX 6W
	consumption	
	Protection level	IP64

Support APP: Icsee