



Camera	RV-ABZ100IPW-5MX
Sensor	1/2.7" CMOS SC2232
Output pixel	1920x1080/30fps
	1920x1080/25fps
Lens	2.8mm-12mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
S/N Ratio	≥50dB
Dome	
wifi chipset	8188eus
WiFi standards	protocol: 802.11b/g/n, max 72Mbps
WiFi frequency band	2412MHz-2472MHz
WiFi safe mode	Open, WPA-PSK, WPA2-PSK
Video compression	H.264/M-JPEG
audio compression	G711, PCM
Mobile View	Android iOS
network safety	HTTPS, 802.1X, IP ADDRESS FILTERING
Rotation Range	Pan:0°~220°, Tilt:-45°~40°
Rotation Speed	Pan:0~30°/s, Tilt:0~25°/s
Preset Points	220pcs presets (dwell time 01-60s interval available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
AB scan range	Any point in range:-45°~40° and 0°~360°
AB scan speed	1-9 grades
Operating temperature	Outdoor: -40℃~+60℃
Operation menu	English/Chinese
Lightning Protection	Transient voltage 6000V
IR distance	Up to 100 meters